10/526197

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



) HERTE BUNGTEN IN ORDER HERT BERG BORG BORG IN HA FRANK HERTE HALT BUNG BUNG BUNG BERGE BERG BERG HER FOR FR

(43) International Publication Date 18 March 2004 (18.03.2004)

PCT

(10) International Publication Number WO 2004/023656 A1

- (51) International Patent Classification7: H03L 7/093, 7/18
- (21) International Application Number:

PCT/IB2003/003771

- (22) International Filing Date: 22 August 2003 (22.08.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

- (30) Priority Data: 0220616.7 5 September 2002 (05.09.2002) GB
- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SPENCER, Adrian,


G. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB). MAR-SHALL, Paul, R. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).

- (74) Agent: WHITE, Andrew; Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

80

[Continued on next page]

(54) Title: IMPROVEMENTS RELATING TO PHASE-LOCK LOOPS



(57) Abstract: A phase lock loop comprises a variable frequency oscillator (20), a divider (30), a phase comparator (40), a gain control stage (240), and a loop filter (50). The frequency response of the loop is measured by superimposing a modulation at a number of different rates on the error signal generated by the phase comparator, and by measuring for each modulation rate the peak-to-peak variation of the loop control signal controlling the oscillator frequency. If, due to errors in component values, the frequency response deviates from its desired value, the loop gain is adjusted to bring the frequency response close to its desired value.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.